AM4115ZTW



Brand: Product Code: AM4115ZTW - EDGE

Short Description

1.3 Megapixel resolution Versatility due to exchangeable caps 10-50x magnification Polarizer (anti-reflection) Macro zoom

Description

The Dino-Lite Edge models provide superior image quality and a high level of flexibility due to the adaptable cap design. The built-in adjustable polarizer reduces glare and reflection on shiny objects.

This model can work with 2 magnification rates while maintaining the same working distance, making this the ideal model for macro view applications with a larger field of view and a zoom function to reveal smaller details. Different caps are supplied with the microscope making the Dino-Lite Edge the perfect choice for any professional application.



Measurement uluuluulu functionality



Adjustable ~10-50x



» Also available: AM4115TW - Edge without Polarizer

Working distance/field of view/depth of field T Zone (Macro zoom/ Larger magnification)

MAGNIFICAT ON	I WORKING DISTANCE	FOV(X)	FOV(Y)	DOF
Listed values may differ slightly				Unit = mm
15	182	30	24	39
20	119	23	19	21
30	64	15	12	9
40	42	11	9	5
50	14	9	7	3
	W Zone (S	Standard zoom/ L	arger FOV)	
MAGNIFICAT: ON	I WORKING DISTANCE	FOV(X)	FOV(Y)	DOF
		FOV(X)	FOV(Y)	DOF Unit = mm
ON Listed values may differ		FOV(X) 98	FOV(Y) 78	
ON Listed values may differ slightly	DISTANCE			Unit = mm
ON Listed values may differ slightly 5	DISTANCE 156	98	78	Unit = mm 250
ON Listed values may differ slightly 5 10	DISTANCE 156 68	98 41	78 33	Unit = mm 250 51

Specification	
Lighting	
Light/ LED type	White
Number of LEDs	8
LED on/off switchable:	Yes
Infrared filter	IR cut-filter >650 nm
Diffuser available	Yes (N3C-D included)
Emission filter	No
Polarizer	Yes, linear
Optics	
Magnification	10-50x
Macro zoom	Nee
Working distance	Standard
Lens type	Glass with anti-reflection coating
Sensor	
Sensor type	CMOS
Resolution	1.3 Megapixel (1280x1024)
Maximum frame rate	30 fps
Compatibility	
Interface	USB 2.0
Operating system	Windows 7, 8, 10 & 11, MacOS 10.9 and up
Software	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)
Supported image formats (Windows)	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX
Supported video formats	WMV, FLV, SWF
(Windows)	
Supported image formats (MacOS)	JPEG, PNG
Supported video formats (MacOS)	MOV
Imaging standards	DirectShow, UVC
Wifi	Wireless-ready, requires the WF-10 WiFi streamer (optional)
Housing	
Housing material	Composite/ plastic housing
Magnification lock	Yes
Dimensions	10.5cm (L) x 3.2cm (D)
Weight	100g
Cable length	1.8m
Features	
Special feature	Macro zoom
1	

Yes
Yes
No
Microscope, carry pouch, software CD, calibration target, user manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- diffuser cap, N3C-E- Extension cap, N3C-L- Long cap, N3C-S- Side light cap
2 years European warranty
CE, FCC, ROHS
€600,00 - €800,00

Product Gallery







