Dino-Lite Europe - Phone: - Email:

AF7515MT4A



Marke:

Artikelnummer: AF7515MT4A

Short Description

High Optical Resolution
5.0 Megapixel
Coaxial-Brightfield Illumination
Flexible LED Control (FLC, coaxial light)
Automatic Magnification Readout (AMR)
Adaptable Interface
Robust Metal Housing

Beschreibung

Integrated with coaxial lighting for viewing reflective surfaces, AF7515MT4A is a 5-megapixel microscope delivering exceptional brightfield imaging at 420x ~ 470x magnification. Through the use of FLC, this model can offer clear visualization of different topographical features such as edges, dents, and pores. AF7515MT4A is also compatible with the optional WF-20 Wi-Fi streamer, providing users with added convenience for wireless streaming applications

Working distance/field of view/depth of field

M	WD	FOV (x)	FOV (y)	DOF
420	6.7	0.94	0.71	0.04

430	7.7	0.92	0.69	0.04
440	8.6	0.90	0.67	0.04
450	8.6	0.88	0.66	0.04
460	8.5	0.86	0.65	0.03
470	8.4	0.84	0.63	0.03

Spezifikation

Spezinkation			
Lighting			
Light/ LED type	White		
Optics			
Magnification	$420x \sim 470x$		
Sensor			
Resolution	5.0 Megapixel (2592 x 1944)		
Maximum frame rate	10 fps at 5.0 MP/3.0 MP, MJPEG 25 fps at 1.3 MP, MJPEG 3 www.dino-lite.com 30 fps at VGA, MJPEG 10 fps at 1.3 MP, YUY2		
Compatibility			
Interface	USB 2.0		
Operating system	Windows 7/8/10/11 macOS 10.14 or later		
Housing			
Magnification lock	Yes		
Dimensions	117 mm (H) x 34 mm (D)		
Weight	Approx. 101 g		
Cable length	Approx. 1.8 m		
Features			
Measurement	Yes		
Calibration	Yes		
Microtouch sensor	Yes		
Information			
Package contents	Microscope, Carry pouch, calibration target, user manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- diffuser cap, N3C-E- extension cap, N3C-L- Long cap, N3C-S- Side light cap		
Warranty information	2 years European warranty		
Regulatory approval	CE, FCC, ROHS		