Dino-Lite Europe - Phone: - Email:

AM2111



Short Description

640x480 Resolution 4 white LEDs (non-switchable) 10-70, 200x magnification Economic choice for consumer use

Descrizione

The AM2111 Dino-Lite Basic is the entry level Dino-Lite USB microscope without compromise on product quality. It offers VGA resolution imaging (640x480), LED illumination, tough composite housing and a variable magnification of 10~70x and 200x.



In addition, the series offers video frame rates up to 30 fps and the ability to save files in BMP, JPG and AVI format. Professional-quality imaging results can be viewed on any computer via high speed USB 2.0 output and the included DinoCapture (for PC) or DinoXcope (for MAC) software. The Dino-Lite AM2111 Basic is an excellent choice for hobbyists, schools, kids or any other cost sensitive application.

Working distance/field of view/depth of field						
	MAGNIFICATI	WORKING	FIELD OF	FIELD OF	DEPTH OF	
	ON RATE	DISTANCE	VIEW(X)	VIEW(Y)	FIELD	
	Listed values				Unit = mm	
	may differ					
	slightly					
	20	51.7	25.0	15.7	8.02	
	30	24.1	14.0	10.5	-	
	40	11.0	10.5	7.9	-	
	50	3.8	8.4	6.3	1.95	
	60	-0.6	7.0	5.2	-	
	200	-0.4	2.1	1.6	0.46	
	210	0.6	2.0	1.5	-	
	220	1.7	1.9	1.4	-	

1.8

1.4

Specifiche

2.8

230

Light/ LED type White Number of LEDs 4 LED on/off switchable: No Infrared filter IR cut-filter >650 nm Diffuser available No Emission filter No Polarizer No Optics Magnification 20-50x, 200x	
Number of LEDs LED on/off switchable: Infrared filter IR cut-filter >650 nm Diffuser available No Emission filter No Polarizer No Optics	
LED on/off switchable: No Infrared filter IR cut-filter >650 nm Diffuser available No Emission filter No Polarizer No Optics	
Infrared filter IR cut-filter >650 nm Diffuser available No Emission filter No Polarizer No Optics	
Diffuser available No Emission filter No Polarizer No Optics	
Emission filter No Polarizer No Optics	
Polarizer No Optics	
Optics	
-	
Magnification 20-50x, 200x	
Macro zoom No	
Working distance Standard	
Lens type Glass with anti-reflection coating	
Sensor	
Sensor type CMOS	
Resolution VGA (640x480)	
Maximum frame rate 30 fps	
Compatibility	
Interface USB 2.0	
Operating system Windows 7, 8, 10 & 11, MacOS 10.9 and up	
Software DinoCapture 2.0 (Windows), DinoXcope (Mac	

	OS)		
Supported image formats	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA,		
(Windows)	PCX, MNG, WBMP, JP2, JPC, PGX		
Supported video formats	WMV, FLV, SWF		
(Windows)			
Supported image formats	JPEG, PNG		
(MacOS)			
Supported video formats	MOV		
(MacOS)			
Imaging standards	DirectShow, UVC		
Wifi	No		
Housing			
Housing material	Composite/ plastic housing		
Magnification lock	No		
Dimensions	10.5cm (L) x 3.2cm (D)		
Weight	105g		
Cable length	1.8m		
Features			
Special feature	No		
Measurement	No		
Calibration	No		
Microtouch sensor	No		
ESD safe	No		
Information			
Package contents	Microscope, software CD, user manual		
Warranty information	2 years European warranty		
Regulatory approval	CE, FCC, ROHS		
Price range	€0 - €200,00		

Product Gallery



