# AM73515MZT



Marka: Ürün Kodu: AM73515MZT

#### **Short Description**

5 Megapixel Edge sensor USB 3.0, maximum 45fps 10-220x magnification Automatic Magnification Reading (AMR) Flexible LED Control (FLC) Polarizer

#### Aç?klama

With the use of the USB 3.0 connection the AM73515MZT is able to capture smooth and high-quality images. The Edge series optics and the special feature Flexible LED Control (FLC) and Automatic Magnification Reading (AMR) makes the AM73515MZT the best choice for the more demanding applications.

USB 3.0 adds a new transfer mode called "SuperSpeed" (SS) capable of transferring data up to 5Gbits/s (625MB/s). Dino-Lite models with USB 3.0 offer an image transfer speed of up to 45FPS at a 1280 x 960 resolution. SuperSpeed allows you to take advantage of the full power of the Dino-Lite Edge Series optics including improved colour accuracy and image quality. The AMR function automatically detects and displays the magnification of the Dino-Lite. The magnification is displayed within the Dino-Lite software and stored with the captured picture and simplifies the measuring process. The AM73515MZT is one of the most high-end Dino-Lite products available and the toplevel product within the Dino-Lite USB 3.0 range. For professionals who are looking for high speed data transfer, the best available image quality and are looking for advanced features this is the model of choice.



The Dino-Lite AM73515MZT is a USB 3.0 model with a magnification range of 10x - 220x and a standard working distance of up to 6 cm. This model is member of the Dino-Lite Edge family with the latest, cutting-edge optics, an unmatched 5 megapixel sensor and several special features such as Automatic Magnification Reading (AMR), Flexible LED Control (FLC), built-in polarization filter, full metal body, extensive measurement functions, calibration, exchangeable front caps and more.

Optical Data Ta MAGNIFICAT ION RATE		FIELD OF VIEW(X)	FIELD OF VIEW(Y)	DEPTH OF FIELD
10	142.4	37.8	28.3	19.7
20	59.5	19.5	14.6	5.4
30	32.9	13.0	9.7	2.6
40	20.2	9.8	7.3	1.6
50	13.2	7.8	5.8	1.1
60	9.0	6.5	4.8	0.8
70	6.4	5.6	4.2	0.6
80	4.8	4.9	3.6	0.5
90	3.9	4.3	3.2	0.42
100	3.5	3.9	2.9	0.36
110	3.3	3.6	2.7	0.31

120	3.5	3.3	2.4	0.27
130	3.8	3.0	2.2	0.24
140	4.3	2.8	2.1	0.22
150	4.9	2.6	1.9	0.2
160	5.6	2.4	1.8	0.18
170	6.4	2.3	1.7	0.17
180	7.3	2.2	1.6	0.15
190	8.2	2.1	1.5	0.14
200	9.2	2.0	1.5	0.13
210	10.2	1.9	1.4	0.13
220	11.3	1.8	1.3	0.12
Listed values	*Without front	t		Unit = mm
may differ slightly	сар			

## Özellikler

O Lemmer			
Lighting			
Light/ LED type	White		
Number of LEDs	8		
LED on/off switchable:	Yes		
Infrared filter	IR cut-filter >650 nm		
Diffuser available	Yes (N3C-D included)		
Emission filter	No		
Polarizer	Yes, linear		
Optics			
Magnification	10-220x		
Macro zoom	No		
Working distance	Standard		
Lens type	Glass with anti-reflection coating		
Sensor			
Sensor type	CMOS		
Resolution	5 Megapixel (2560x1920)		
Maximum frame rate	45fps (max 20fps video recording)		
Compatibility			
Interface	USB 3.0, Cable included**		
Operating system	Windows7, 8, 10 & 11, MacOS 10.9 and up		
Software	DinoCapture 2.0 (Windows), DinoXcope (Mac		
	OS)		
Supported image formats	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA,		
(Windows)	PCX, MNG, WBMP, JP2, JPC, PGX		
Supported video formats (Windows)	WMV, FLV, SWF		
· /			

Supported image formats (MacOS)	JPEG, PNG		
Supported video formats (MacOS)	MOV (max 1.3MP)		
Imaging standards	DirectShow, UVC		
Wifi	No		
Housing			
Housing material	Metal housing		
Magnification lock	Yes		
Dimensions	11.9cm (L) x 3.3cm (H)		
Weight	110g		
Cable length	1.8m		
Features			
Special feature	Automatic Magnification Reading (AMR) Flexible LED Control (FLC)		
Measurement	Yes		
Calibration	Yes		
Microtouch sensor	Yes		
ESD safe	Yes		
Information			
Package contents	Microscope, carry pouch, software CD, user manual, quick guide, calibration target, front cover N3C-O- Open cap, N3C-C- Closed cap, N3C-D- Diffuser cap, N3C-E- Extension cap, N3C-L- Long cap, N3C-S- Side light cap		
Warranty information	2 years European warranty		
Regulatory approval	CE, FCC, ROHS		
Price range	€1100,00 - €1300,00		
Note Product Callery	**Dino-Lite USB 3.0 models use a custom USB-A and USB-C cable that is specifically designed for Dino-Lite		

### **Product Gallery**