# AM7515MT2A



Zna?ka: Kód produktu: AM7515MT2A

#### **Short Description**

5 Megapixel resolution 130x ~ 220x magnification Coaxial and brightfield illumination Flexible LED Control (FLC) Automatic Magnification Reading (AMR)

#### **Popis**

The AM7515MT2A is a 5MP Dino-Lite Edge Series microscope that has a magnification range of  $130x \sim 220x$  with built-in coaxial illumination. By using the Flexible LED Control (FLC), this model is capable of switching between or mixing, brightfield and coaxial illumination.





The coaxial illumination technique reveals details that are very difficult to see under normal light. The AM7515MT2A includes the Automatic Magnification Reading (AMR) feature which automatically detects and displays the magnification in the included Dino-Lite software.

These unique features make the Dino-Lite AM7515MT2A a great inspection tool for material analysis, electronics inspection, or any similar application that requires coaxial illumination, versatility and mobility. The Dino-Lite AM7515MT2A is bundled with the user-friendly DinoCapture 2.0 software for Windows.

### For this model it includes functions such as:

- Automatic Magnification Reading (AMR)
- Flexible LED Control (FLC)
- Calibration
- Measurement
- Capturing & annotating images
- And recording video

#### Working distance/field of view/depth of field

working distance/new or view/depth of new					
MAGNIFICAT	I WORKING	FIELD OF	FIELD OF	<b>DEPTH OF</b>	
<b>ON RATE</b>	<b>DISTANCE*</b>	VIEW(X)	VIEW(Y)	FIELD	
130	4.5	3.0	2.2		
140	5.0	2.8	2.1		
150	5.6	2.6	1.9		
160	6.3	2.4	1.8		
170	7.1	2.3	1.7		
180	8.0	2.2	1.6		
190	8.9	2.1	1.5		
200	9.9	2.0	1.5		

210	10.9	1.9	1.4	
220	11.9	1.8	1.3	0.1
Listed values	*Without front			Unit = mm
may differ	cap			
slightly				

## Specifikace

Speenmace			
Lighting			
Light/ LED type	White		
Number of LEDs	8		
LED on/off switchable:	Yes		
Infrared filter	IR cut-filter >650 nm		
Diffuser available	Yes, N3C-D		
Emission filter	No		
Polarizer	No		
Optics			
Magnification	130x ~ 220x		
Macro zoom	No		
Working distance	Standard		
Lens type	Glass with anti-reflection coating		
Sensor			
Sensor type	CMOS		
Resolution	5.0 Megapixel (2592x1944)		
Maximum frame rate	30fps (max 20fps video recording)		
Compatibility			
Interface	USB 2.0		
Operating system	Windows 7, 8, 10 & 11, MacOS 10.12 and up		
Software	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)		
Supported image formats (Windows)	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX		
Supported video formats	WMV, FLV, SWF		
(Windows)			
Supported image formats	JPEG, PNG		
(MacOS)			
Supported video formats	MOV (max 1.3MP)		
(MacOS)			
Imaging standards	DirectShow, UVC		
Wifi	Wireless-ready, requires the WF-10 WiFi streamer		
	(optional)		
Housing			
Housing material	Metal housing		

Magnification lock	Yes
Dimensions	10.7cm (L) x 3.2cm (D)
Weight	139g
Cable length	1.8m
Features	
Special feature	Automatic Magnification Reading (AMR),
	Flexible LED Control (FLC), Coaxial illumination
Measurement	Yes
Calibration	Yes
Microtouch sensor	Yes
ESD safe	Yes
Information	
Package contents	Microscope, Carry pouch, Software CD, User
	manual, Quick guide, Calibration target, Front
	cover box
Warranty information	2 years European warranty
Regulatory approval	CE, FCC, ROHS
Price range	€1000,00 - €1200,00
Product Gallery	