## AM4115ZTW



**Marke:** Artikelnummer: AM4115ZTW - EDGE

## **Short Description**

1.3 Megapixel resolutionVersatility due to exchangeable caps10-50x magnificationPolarizer (anti-reflection)Macro zoom

## **Beschreibung**

The Dino-Lite Edge models provide superior image quality and a high level of flexibility due to the adaptable cap design. The built-in adjustable polarizer reduces glare and reflection on shiny objects.

This model can work with 2 magnification rates while maintaining the same working distance, making this the ideal model for macro view applications with a larger field of view and a zoom function to reveal smaller details. Different caps are supplied with the microscope making the Dino-Lite Edge the perfect choice for any professional application.



Measurement Illuuluului functionality





» Also available: AM4115TW - Edge without Polarizer

## Working distance/field of view/depth of field T Zone (Macro zoom/ Larger magnification)

MAGNIFICAT ON	I WORKING DISTANCE	FOV(X)	FOV(Y)	DOF
Listed values may differ slightly				Unit = mm
15	182	30	24	39
20	119	23	19	21
30	64	15	12	9
40	42	11	9	5
50	14	9	7	3
	W Zone (S	Standard zoom/ L	arger FOV)	
MAGNIFICAT: ON	I WORKING DISTANCE	FOV(X)	FOV(Y)	DOF
		FOV(X)	FOV(Y)	DOF Unit = mm
ON Listed values may differ		FOV(X) 98	FOV(Y) 78	
ON Listed values may differ slightly	DISTANCE			Unit = mm
ON Listed values may differ slightly 5	<b>DISTANCE</b> 156	98	78	<b>Unit = mm</b> 250
ON Listed values may differ slightly 5 10	<b>DISTANCE</b> 156 68	98 41	78 33	<b>Unit = mm</b> 250 51

Spezifikation				
Lighting				
Light/ LED type	White			
Number of LEDs	8			
LED on/off switchable:	Yes			
Infrared filter	IR cut-filter >650 nm			
Diffuser available	Yes (N3C-D included)			
Emission filter	No			
Polarizer	Yes, linear			
Optics				
Magnification	10x ~ 50x			
Macro zoom	Nee			
Working distance	Standard			
Lens type	Glass with anti-reflection coating			
Sensor				
Sensor type	CMOS			
Resolution	1.3 Megapixel (1280x1024)			
Maximum frame rate	30 fps			
Compatibility				
Interface	USB 2.0			
Operating system	Windows 7, 8, 10 & 11, MacOS 10.9 and up			
Software	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)			
Supported image formats	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA,			
(Windows)	PCX, MNG, WBMP, JP2, JPC, PGX			
Supported video formats (Windows)	WMV, FLV, SWF			
Supported image formats (MacOS)	JPEG, PNG			
Supported video formats (MacOS)	MOV			
Imaging standards	DirectShow, UVC			
Wifi	Wireless-ready, requires the WF-10 WiFi streamer (optional)			
Housing				
Housing material	Composite/ plastic housing			
Magnification lock	Yes			
Dimensions	10.5cm (L) x 3.2cm (D)			
Weight	100g			
Cable length	1.8m			
Features				
Special feature	Macro zoom			
1				

Yes
Yes
No
Microscope, carry pouch, software CD, calibration target, user manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- diffuser cap, N3C-E- Extension cap, N3C-L- Long cap, N3C-S- Side light cap
2 years European warranty
CE, FCC, ROHS
€600,00 - €800,00

**Product Gallery** 







