Dino-Lite Europe - Phone: - Email:

AM4515T8 - EDGE

Artikelnummer: AM4515T8




Short Description

1.3 Megapixel resolutionVersatility due to exchangeable caps700-900x magnificationAutomatic Magnification Reading (AMR)

Beschreibung

With up to 900x magnification and high-resolution optics, this high magnification Dino-Lite model reveals details as small as 1.5 micrometer (µm). It also features a greater working distance at high magnification making it easier to watch and move very small objects under the microscope.



These unique features make the Dino-Lite AM4515T8 a great inspection tool for

biomedical and scientific research, material analysis, electronics inspection, or any similar application that require high magnification, versatility and mobility. The Dino-Lite AM4515T8 is bundled with the user-friendly DinoCapture 2.0 software. For this model it includes functions such as Automatic Magnification Reading (AMR), calibration, measurement, capturing & annotating images, and recording video. Although the AM4515T8 model can be operated handheld, a high-precision stand is recommended. The Dino-Lite RK-10A for example is a great add-on, it is a sturdy and stable high-end stand solution constructed of resilient stainless steel and lightweight aluminum and offers a very precise fine-focus adjustment.

MAGNIFICATI ON RATE Listed values may differ slightly	WORKING DISTANCE * * Without front cap	FIELD OF VIEW(X)	FIELD OF VIEW(Y)	DEPTH OF FIELD Unit = mm
700	6.6	0.6	0.4	
800	6.4	0.5	0.4	
900	6.3	0.4	0.3	0.016

Spezifikation

Spezifikation .			
Lighting	ng		
Light/ LED type	White		
Number of LEDs	8		
LED on/off switchable:	Yes		
Infrared filter	IR cut-filter >650 nm		
Diffuser available	No		
Emission filter	No		
Polarizer	No		
Optics			
Magnification	$700x \sim 900x$		
Macro zoom	No		
Working distance	Standard		
Lens type	Glass with anti-reflection coating		
Sensor			
Sensor type	CMOS		
Resolution	1.3 Megapixel (1280x1024)		
Maximum frame rate	30 fps		
Compatibility			
Interface	USB 2.0		
1	·		

Operating system	Windows 7,8,10 & 11, MacOS 10.9 and up			
Software	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)			
Supported image formats (Windows)	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX			
Supported video formats (Windows)	WMV, FLV, SWF			
Supported image formats (MacOS)	JPEG, PNG			
Supported video formats (MacOS)	MOV			
Imaging standards	DirectShow, UVC			
Wifi	Wireless-ready, requires the WF-10 WiFi streamer (optional)			
Housing				
Housing material	Composite/ plastic housing			
Magnification lock	Yes			
Dimensions	10.3 cm (L) x 3.2cm (D)			
Weight	100g			
Cable length	1.8m			
Features				
Special feature	Automatic Magnification Reading (AMR)			
Measurement	Yes			
Calibration	Yes			
Microtouch sensor	Yes			
ESD safe	No			
Information				
Package contents	Microscope, carry pouch, software CD, calibration			
	target, user manual, N3C-O- Open cap, N3C-C-			
	Closed cap, N3C-E- Extension cap			
Warranty information	2 years European warranty			
Regulatory approval	CE, FCC, ROHS			
Price range	€700,00 - €900,00			

Product Gallery

