Dino-Lite Europe - Phone: - Email:

AM8917MT4A

Brand:

Product Code: AM8917MT4A

Short Description

8.0 Megapixel

Enhanced Flexible LED Control (eFLC, with coaxial light)

Depth Acquisition (DPQ)

Extended Depth of Field (EDOF)

Automatic Magnification Readout (AMR)

Description

The AM8917MT4A is a feature-packed microscope integrated with coaxial light and EDOF, answering needs for inspecting reflective surfaces and capturing all-in-focus images under 400x magnification. AM8917MT4A includes advanced features such as DPQ, EDR, AMR, and both Auto and Manual Refocusing.

Working distance/field of view/depth of field

M	WD	FOV (x)	FOV (y)	DOF
415	8.6	1.46	0.82	0.04
420	8.6	1.44	0.81	0.04
430	8.5	1.41	0.79	0.04
440	8.5	1.38	0.78	0.04
450	8.4	1.35	0.76	0.04
460	8.4	1.32	0.74	0.04

Specification

Lighting		
Light/ LED type	White LED	
Optics		
Magnification	$415x \sim 460x$	
Sensor		
Resolution	8.0 Megapixel (3840x2160)	
Maximum frame rate	10 fps at 8.0 MP, MJPEG 25 fps at 2.0 MP,	
	MJPEG	
Compatibility		

Interface	USB 2.0			
Operating system	Windows 10/11 macOS 10.14 or later			
Supported image formats	DinoCapture 2.0: BMP, GIF, PNG, MNG, TIF,			
(Windows)	TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS, PNM			
Supported video formats (Windows)	DinoCapture 2.0: WMV, FLV, SWF			
Supported image formats (MacOS)	DinoXcope: PNG, JPEG			
Supported video formats (MacOS)	DinoXcope: MOV			
Housing				
Magnification lock	Yes			
Dimensions	133 mm (H) x 32 mm (D)			
Weight	Approx. 124 g			
Cable length	Approx. 1.8 m			
Features				
Measurement	Yes			
Calibration	Yes			
Microtouch sensor	Yes			
Information				
Package contents	Microscope, carry pouch, calibration target, user manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- diffuser cap, N3C-E- Extension cap, N3C-L- Long cap, N3C-S- Side light cap			
Warranty information	2 years European warranty			
Regulatory approval	CE, FCC, ROHS			