# AM8917MT8A

# Brand: Product Code: AM8917MT8A

## **Short Description**

8.0 MegapixelEnhanced Flexible LED Control (eFLC, with coaxial light)Depth Acquisition (DPQ)Extended Depth of Field (EDOF)Automatic Magnification Readout (AMR)

### Description

Equipped with coaxial light, EDOF, and many other sophisticated features, AM8917MT8A is an 800x microscope ideal for viewing reflective surfaces and delivering all-in-focus images. The AM8917MT8A includes DPQ, EDR, AMR, and Auto and Manual Refocusing.

#### Working distance/field of view/depth of field

| Μ   | WD  | FOV (x) | FOV (y) | DOF  |
|-----|-----|---------|---------|------|
| 700 | 5.8 | 0.87    | 0.49    | 0.01 |
| 750 | 5.7 | 0.81    | 0.46    | 0.01 |
| 800 | 5.6 | 0.76    | 0.43    | 0.01 |
| 850 | 5.6 | 0.71    | 0.40    | 0.01 |
| 900 | 5.5 | 0.68    | 0.38    | 0.01 |

#### Specification

| ▲                  |   |
|--------------------|---|
| Lighting           |   |
| Light/ LED type    | White LED                                 |
| Optics             |   |
| Magnification      | 700x ~ 900x                               |
| Sensor             |   |
| Resolution         | 8.0 Megapixel (3840x2160)                 |
| Maximum frame rate | 10 fps at 8.0 MP, MJPEG 25 fps at 2.0 MP, |
|                    | MJPEG                                     |
| Compatibility      |   |
| Interface          | USB 2.0                                   |
|                    |   |

| Operating system                     | Windows 10/11 macOS 10.14 or later  |  |  |  |
|--------------------------------------|---|--|--|--|
| Supported image formats              | DinoCapture 2.0: BMP, GIF, PNG, MNG, TIF,   |  |  |  |
| (Windows)                            | TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS, PNM  |  |  |  |
| Supported video formats<br>(Windows) | DinoCapture 2.0: WMV, FLV, SWF  |  |  |  |
| Supported image formats (MacOS)      | DinoXcope: PNG, JPEG  |  |  |  |
| Supported video formats (MacOS)      | DinoXcope: MOV  |  |  |  |
| Housing                              |   |  |  |  |
| Magnification lock                   | Yes   |  |  |  |
| Dimensions                           | 133 mm (H) x 32 mm (D)  |  |  |  |
| Weight                               | Approx. 124 g   |  |  |  |
| Cable length                         | Approx. 1.8 m   |  |  |  |
| Features                             |   |  |  |  |
| Special feature                      | EDOF, EDR, DPQ, and Auto/Manual Refocus are available on Windows PC only.   |  |  |  |
| Measurement                          | Yes   |  |  |  |
| Calibration                          | Yes   |  |  |  |
| Microtouch sensor                    | Yes   |  |  |  |
| Information                          |   |  |  |  |
| Package contents                     | Microscope, carry pouch, calibration target, user<br>manual, N3C-O- Open cap, N3C-C- Closed cap,<br>N3C-D- diffuser cap, N3C-E- Extension cap, N3C-<br>L- Long cap, N3C-S- Side light cap |  |  |  |
| Warranty information                 | 2 years European warranty   |  |  |  |
| Regulatory approval                  | CE, FCC, ROHS   |  |  |  |