Dino-Lite Europe - Phone: - Email:

# AM8917MT8



**Brand:** 

**Product Code:** AM8917MT8

#### **Short Description**

8.0 Megapixel
Enhanced Flexible LED Control (eFLC)
Depth Acquisition (DPQ)
Extended Depth of Field (EDOF)
Automatic Magnification Readout (AMR)

#### **Description**

Introducing EDOF on AM8917MT8 for generating images with an extended depth of field, this 8-megapixel  $700x \sim 900x$  digital microscope provides a clear imaging experience and is equipped with a range of tools for professional use such as DPQ, refocus mode, AMR, and eFLC.

### Working distance/field of view/depth of field

M	WD	FOV (x)	FOV (y)	DOF
700	5.8	0.87	0.49	0.01
750	5.7	0.81	0.46	0.01
800	5.6	0.76	0.43	0.01
850	5.6	0.71	0.40	0.01
900	5.5	0.68	0.38	0.01

## **Specification**

Lighting				
Light/ LED type	White LEDs			
Optics				
Magnification	$700x \sim 900x$			
Sensor				
Resolution	8.0 Megapixel (3840 x 2160)			
Maximum frame rate	10 fps at 8.0 MP, MJPEG 25 fps at 2.0 MP,			
	MJPEG			
Compatibility				
Interface	USB 2.0			
Operating system	Windows 10/11 macOS 10.14 or later			
Supported image formats	DinoCapture 2.0: BMP, GIF, PNG, MNG, TIF,			
(Windows)	TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS,			
	PNM			
Supported video formats	DinoCapture 2.0: WMV, FLV, SWF			
(Windows)				
Supported image formats	DinoXcope: PNG, JPEG			
(MacOS)				
Supported video formats	DinoXcope: MOV			
(MacOS)				
Housing				
Magnification lock	Yes			
Dimensions	133 mm (H) x 32 mm (D)			
Weight	Approx. 120 g			
Cable length	Approx. 1.8 m			
Features				
Measurement	Yes			
Calibration	Yes			
Microtouch sensor	Yes			
Information				
Package contents	Microscope, carry pouch, calibration target, user			
	manual, N3C-O- Open cap, N3C-C- Closed cap,			
	N3C-D- diffuser cap, N3C-E- Extension cap, N3C-			
	L- Long cap, N3C-S- Side light cap			
Warranty information	2 years European warranty			
Regulatory approval	CE, FCC, ROHS			