Dino-Lite Europe - Phone: - Email:

# AM8917MT4A

**Brand:** 

**Product Code:** AM8917MT4A

### **Short Description**

8.0 Megapixel

Enhanced Flexible LED Control (eFLC, with coaxial light)

Depth Acquisition (DPQ)

Extended Depth of Field (EDOF)

Automatic Magnification Readout (AMR)

#### **Description**

The AM8917MT4A is a feature-packed microscope integrated with coaxial light and EDOF, answering needs for inspecting reflective surfaces and capturing all-in-focus images under 400x magnification. AM8917MT4A includes advanced features such as DPQ, EDR, AMR, and both Auto and Manual Refocusing.

## Working distance/field of view/depth of field

M	WD	FOV (x)	FOV (y)	DOF
415	8.6	1.46	0.82	0.04
420	8.6	1.44	0.81	0.04
430	8.5	1.41	0.79	0.04
440	8.5	1.38	0.78	0.04
450	8.4	1.35	0.76	0.04
460	8.4	1.32	0.74	0.04

#### **Specification**

Lighting	
Light/ LED type	White LED
Optics	
Magnification	$415x \sim 460x$
Sensor	
Resolution	8.0 Megapixel (3840 x 2160)
Maximum frame rate	10 fps at 8.0 MP, MJPEG 25 fps at 2.0 MP,
	MJPEG
Compatibility	

Interface	USB 2.0	
Operating system	Windows 10/11 macOS 10.14 or later	
Supported image formats	DinoCapture 2.0: BMP, GIF, PNG, MNG, TIF,	
(Windows)	TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS, PNM	
Supported video formats (Windows)	DinoCapture 2.0: WMV, FLV, SWF	
Supported image formats (MacOS)	DinoXcope: PNG, JPEG	
Supported video formats (MacOS)	DinoXcope: MOV	
Housing		
Magnification lock	Yes	
Dimensions	133 mm (H) x 32 mm (D)	
Weight	Approx. 124 g	
Cable length	Approx. 1.8 m	
Features		
Measurement	Yes	
Calibration	Yes	
Microtouch sensor	Yes	
Information		
Package contents	Microscope, carry pouch, calibration target, user manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- diffuser cap, N3C-E- Extension cap, N3C-L- Long cap, N3C-S- Side light cap	
Warranty information	2 years European warranty	
Regulatory approval	CE, FCC, ROHS	