AM5216TF



Marka: Ürün Kodu: AM5216TF

Short Description

Extra-long working distance High optical resolution D-sub interface Microtouch button Interchangeable front caps

Aç?klama

Designed to provide extra-long working distance, the Dino-Lite Edge D-sub series AM5216TF offers minimum 108mm viewing distance at maximum 70X magnification. Through direct connection to VGA monitors, the AM5216TF can be well-suited for inspection, quality control, failure analysis, etc.





The main features of the AM5216TF are:

• Extra-long working distance

High speed

- High optical resolution
- D-sub interface
- Microtouch button
- Interchangeable front caps
- And more...

Working distance/field of view/depth of field

| working distance/netd of view/depth of netd | | | | | |
|---|----------|----------|----------|-----------|--|
| MAGNIFICATI | WORKING | FIELD OF | FIELD OF | DEPTH OF | |
| ON RATE | DISTANCE | VIEW(X) | VIEW(Y) | FIELD | |
| Listed values | | | | Unit = mm | |
| may differ | | | | | |
| slightly | | | | | |
| 10 | 503 | 39.1 | 31.3 | 31.49 | |
| 20 | 271 | 19.5 | 15.6 | 8.67 | |
| 30 | 196 | 13.0 | 10.4 | 4.20 | |
| 40 | 159 | 9.8 | 7.8 | 2.56 | |
| 50 | 135 | 7.8 | 6.3 | 1.76 | |
| 60 | 120 | 6.5 | 5.2 | 1.31 | |
| 70 | 108 | 5.6 | 4.5 | 1.03 | |
| | | | | | |

Özellikler

| Lighting | ing | | |
|------------------------|------------------------------------|--|--|
| Light/ LED type | White | | |
| Number of LEDs | 8 | | |
| LED on/off switchable: | Yes | | |
| Emission filter | No | | |
| Polarizer | No | | |
| Optics | | | |
| Magnification | 10x ~ 70x | | |
| Macro zoom | Yes | | |
| Working distance | Long | | |
| Lens type | Glass with anti-reflection coating | | |
| Sensor | sor | | |
| Sensor type | CMOS | | |
| Resolution | 1280x720 (720p) | | |

| Maximum frame rate | 60 fps | | |
|----------------------|---|--|--|
| Compatibility | | | |
| Interface | VGA (D-Sub) | | |
| Housing | | | |
| Housing material | Composite/ plastic housing | | |
| Magnification lock | No | | |
| Dimensions | 10.5cm (H) x 3.2cm (D) | | |
| Weight | 105g | | |
| Features | | | |
| Special feature | No | | |
| Measurement | No | | |
| Calibration | No | | |
| Microtouch sensor | Yes | | |
| ESD safe | No | | |
| Information | | | |
| Package contents | Microscope, carry pouch, power adapter, front | | |
| | cover box, user manual | | |
| Warranty information | 2 years European warranty | | |
| Regulatory approval: | CE, FCC, ROHS | | |
| Price range | €519,00 - €719,00 | | |