Dino-Lite Europe - Phone: - Email:

AM3111

Marka:

Ürün Kodu: AM3111

Short Description

640x480 Resolution 8 white LEDs 20-50, 200x magnification 60 fps

Aç?klama

The AM3111 digital microscope is an economical pick that provides smooth imaging and balanced color performance, making it suitable for a variety of applications, such as simple industrial inspections, educational use, or personal hobbies.



Overview

Smooth Imaging

The CMOS image sensor transmits smooth images at up to 60 fps with 640 x 480 resolution.

Adjustable Magnification

The adjustable magnification ranges from $20x \sim 50x$ for a broad view to over 200x for detailed close-ups, easily controlled with the focus knob.

Optical Data Table

may differ				
Listed values				Unit = mm
ON RATE	DISTANCE	VIEW(X)	VIEW(Y)	FIELD
MAGNIFICATI	WORKING	FIELD OF	FIELD OF	DEPTH OF

slightly				
20x	64	20	15	14
30x	34	13	10	7
40x	20	10	7	4
50x	13	8	6	3
200x	5	2	1	0.3

Özellikler

Light/ LED type White Number of LEDs 8 Infrared filter IR cut-filter >650 nm Diffuser available No Emission filter No Polarizer No Optics Magnification 20x ~ 50x, 200x Macro zoom No Working distance Standard Lens type Glass with anti-reflection Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate Compatibility Interface USB 2.0	coating
Number of LEDs Infrared filter Diffuser available Emission filter Polarizer Optics Magnification Working distance Lens type Sensor Sensor type Resolution No Resolution No Resolution No Resolution No Resolution No Resolution No CMOS Resolution Resoluti	coating
Infrared filter IR cut-filter >650 nm Diffuser available No Emission filter No Polarizer No Optics Magnification 20x ~ 50x, 200x Macro zoom No Working distance Standard Lens type Glass with anti-reflection Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate Compatibility	coating
Diffuser available Emission filter No Polarizer No Optics Magnification Macro zoom No Working distance Lens type Glass with anti-reflection Sensor Sensor type Resolution VGA (640x480) Maximum frame rate Compatibility	coating
Emission filter Polarizer No Optics Magnification Macro zoom No Working distance Lens type Glass with anti-reflection Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate Compatibility	coating
Polarizer Optics Magnification 20x ~ 50x, 200x Macro zoom No Working distance Lens type Glass with anti-reflection Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate Compatibility	coating
Optics Magnification 20x ~ 50x, 200x Macro zoom No Working distance Standard Lens type Glass with anti-reflection Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate 60 fps Compatibility	coating
Magnification $20x \sim 50x$, $200x$ Macro zoomNoWorking distanceStandardLens typeGlass with anti-reflectionSensorCMOSResolutionVGA (640x480)Maximum frame rate60 fpsCompatibility	coating
Macro zoom Working distance Lens type Glass with anti-reflection Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate Compatibility	coating
Working distance Lens type Glass with anti-reflection Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate Compatibility	coating
Lens type Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate Compatibility Glass with anti-reflection CMOS 60 fps	coating
Sensor Sensor type CMOS Resolution VGA (640x480) Maximum frame rate Compatibility Sensor type CMOS VGA (640x480)	coating
Sensor type CMOS Resolution VGA (640x480) Maximum frame rate 60 fps Compatibility	
Resolution VGA (640x480) Maximum frame rate 60 fps Compatibility	
Maximum frame rate 60 fps Compatibility	
Compatibility	
_	
Interface USB 2.0	
Operating system Windows 7, 8, 10 & 11, M	MacOS 10.9 and up
Software DinoCapture 2.0 (Window OS)	vs), DinoXcope (Mac
Supported image formats (Windows) BMP, GIF, PNG, JPG, TI PCX, MNG, WBMP, JP2,	· · · · · · · · · · · · · · · · · · ·
Supported video formats WMV, FLV, SWF (Windows)	
Supported image formats JPEG, PNG (MacOS)	
Supported video formats MOV (MacOS)	
Imaging standards DirectShow, UVC	
Wifi No	
Housing	
Housing material Composite/ plastic housin	O.
Magnification lock No	g

Dimensions	10.5cm (L) x 3.2cm (D)
Weight	94g
Cable length	1.8m
Features	
Special feature	No
Measurement	No
Calibration	No
Microtouch sensor	No
ESD safe	No
Information	
Package contents	Microscope, software CD, user manual
Warranty information	2 years European warranty
Regulatory approval	CE, FCC, ROHS
Price range	€150,00 - €250,00

Product Gallery